

	(A)= Uncut Length, base to apex	Length, Base to Orifice - (D)= Orifice Diameter	(B)= Outside Diameter at Base (Brim O.D.)	(C)= Brim Width (approx.)	Total Interior Included Angle at Orifice (3*)
<u>Model No.</u>					
Stock Models					
1	19.1mm (0.750")	A - 2.26D	22.23mm (0.875")	2.0mm (0.080")	25°
2	25.4mm (1.000")	A - 2.26D	27.94mm (1.100")	2.5mm (0.100")	25°
Custom Models -Please email to determine availability.					
5.1	5.08mm (0.200")	A - 1.87 D	6.35mm (0.250")	1.5mm (0.060")	30°
7	6.99mm (0.275")	A - 2.26 D	12.70mm (0.500")	2.2mm (0.085")	25°
10	10.0 mm (0.394")	A - 0.50D	26.0mm (1.024")	2.8mm (0.110")	90°
10.2	10.16mm (0.400")	A - 2.26 D	12.70mm (0.500")	1.9mm (0.075")	25°
11	11.00mm (0.433")	A - 1.07 D	15.00mm (0.591")	1.8mm (0.070")	50°
14	13.97mm (0.550")	A - 1.37 D	13.97mm (0.550")	1.8mm (0.070")	40°
15.4	15.39mm (0.606")	A - 1.87 D	19.05mm (0.750")	3.7mm (0.145")	30°
15.9	15.87mm (16.33")	A - 0.71 D	28.58mm (1.125")	3.0mm (0.120")	70°
16.3	16.33mm (0.643")	A - 0.71 D	27.94mm (1.100")	2.3mm (0.090")	70°
19.6	19.56mm (0.770")	A - 0.96 D	28.58mm (1.125")	3.4mm (0.135")	55°
20.1	20.14mm (0.793")	A - 0.87 D	29.31mm (1.154")	2.3mm (0.090")	60°
25.4	25.40mm (1.000")	A - 0.96 D	34.00mm (1.339")	4.1mm (0.160")	55°
27	27.00mm (1.063")	A - 0.60 D	72.00mm (2.835")	9.0mm (0.355")	80°
27.5	27.51mm (1.083")	A - 1.07 D	45.72mm (1.80")	2.1mm (0.82")	50°
31.8	31.75mm (1.250")	A - 0.87 D	41.66mm (1.640")	2.5mm (0.100")	60°
40	40.00mm (1.575")	A - 0.96 D	50.00mm (1.969")	4.7mm (0.185")	55°
40.5	40.51mm (1.595")	A - 1.07 D	27.94mm (1.100")	1.8mm (0.070")	33.5°
43.4	43.43mm (1.710")	A - 1.87 D	36.07mm (1.420")	6.1mm (0.240")	30°
45.3	45.34mm (1.710")	A - 1.64 D	26.42mm (1.040")	5.0mm (0.197")	34°
47.6	47.63mm (1.875")	A - 1.37 D	37.34mm (1.470")	1.3mm (0.050")	40°
50	50.04mm (1.970")	A - 1.07 D	59.99mm (2.362")	5.8mm (0.230")	50°
50.8	50.80mm (2.000")	A - 2.26 D	24.89mm (0.980")	1.0mm (0.040")	25°
76.2	76.20mm (3.000")	A - 2.26 D	40.64mm (1.600")	2.5mm (0.100")	25°